AC Power Solution

OCONUS

PERKINS TECHNICAL SERVICES, INC.

CONUS

PTS AC Docking Station for Dismounted Tactical Radios in Tactical Operations Centers, Combat Operations Centers, Training Centers, Flight Operations, Maintenance Facilities, Perimeter Control & Buildings Worldwide

Model AS0005-PSC-5

SUPPORTS AN/PSC-5

This product is protected under one or more of the following United States Patents: US6,784,570 B1, US7,227,755 B1, and 7,733,658 B1. Additional Patents are pending.
This is an ITAR controlled item.

AC DOCKING STATION
For Dismounted Tactical Radios

PTS has developed a rugged, lightweight, easy to use AC Docking Station. The Docking Station provides the capability of using AC power worldwide to operate AN/PSC-5 tactical radios in a continuous and cost efficient manner.

The unique slide-in / slide-out design allows for easy use and provides increased flexibility in the use of Tactical Radios without the cost and logistic burden of batteries and other power sources. Worldwide applications include tactical operations centers, range operations, test and maintenance facilities, training sites, deployment and staging checkpoints, and remote control operations.

The PTS AC Docking Station provides units the capability of 24/7/365 use at a fraction of the cost and logistical workload of using batteries.

For more information and / or a demonstration contact:
Dr. Lloyd W. Childs at 256-509-0840 or e-mail at sales@pts-inc.com

GSA Advantage
GS 35F-0673J

PTS is set up to accept AC Docking Station sales using a wide variety of methods:

- SF 30 (Amendment of Solicitation / Modification of Contract)
- SF 1449 (Solicitation / Contract / Order for Commercial Items)
- DD Form 1155 (Order for Supplies or Services)
- Any commercial order format

AC Docking Station AS0005-PSC-5

The Platform has:

- Docking Position for one AN/PSC-5
- A controllable high fidelity 4” Mylar speaker for communication monitoring

Physical Description:
Compact Size — (h) 7.5” x (w) 11.5” x (l) 11.0”
— (h) 19cm x (w) 30cm x (l) 28cm
Lightweight Platform — 8.2 lbs, 4kg
Platform and Case — 22.2 lbs, 10 kg

Features:

- Worldwide AC Voltage Input - 85 to 260 VAC
- Worldwide Frequency Input - 47 to 440 Hz
- Fully Automatic Voltage and Frequency Selection
- Rugged, Self-contained Unit — no specialized cabling required
- Supports Remote Operation of LS-671 Speaker
- Operating Temperature Range: -30°C to 50°C
- Relative humidity: 5% to 95%
- Built-in Power Surge Protection
- Molded Plastic Transit Case

This product is protected under one or more of the following United States Patents: US6,784,570,B1 US7,227,755,B1. Additional Patents are pending

FOR MORE INFORMATION AND/OR A DEMONSTRATION, CONTACT DR. LLOYD W. CHILDS AT 256-509-0840 (Cell) OR E-MAIL sales@pts-inc.com
Perkins Technical Services, Inc.,1318-B Putman Dr. • Huntsville, Alabama 35816 • 256.539 6787 (Office) • 256.551.0787 (FAX) • www.pts-inc.com